

COMPANY WITH  
MANAGEMENT SYSTEM  
- UNI EN ISO 9001 -  
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio  
Via del Fifico, 12 - 40065 Pianoro (BO) - Italia - C.P. 18  
tel. +39 051 770 511 - fax +39 051 777 437  
www.sayerlack.com  
Cod. Fisc. e Reg. Impr. Bo 08866930152  
P. IVA: IT 00494251200 - R.E.A. n. 313180  
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

## Technical Data Sheet

## HARDENERS FOR POLYURETHANES

Supersedes previous issue dated 02/11/11

DATE 06/12/11

As to other characteristics and method of use, please refer to the technical data sheets relating to part A.

CODE	SHELF-LIFE (months)	SOLIDS CONTENT	SPECIFIC GRAVITY
SG0720/00	24	26 ± 1	0.955 ± 0.030
TH0146/00	24	25 ± 1	0.986 ± 0.030
TH0222/00	24	24 ± 1	1.000 ± 0.030
TH0333/00	24	24 ± 1	1.000 ± 0.030
TH0703/00	24	24 ± 1	0.955 ± 0.030
TH0711/00	24	28 ± 1	0.940 ± 0.030
TH0713/00	24	21 ± 1	0.930 ± 0.030
TH0715/00	24	35 ± 1	0.970 ± 0.030
TH0718/00	24	28 ± 1	0.940 ± 0.030
TH0720/00	24	26 ± 1	0.955 ± 0.030
TH0721/00	24	44 ± 1	1.000 ± 0.030
TH0722/00	24	29 ± 1	0.969 ± 0.030
TH0723/00	24	21 ± 1	0.925 ± 0.030
TH0724/00	24	31 ± 1	0.950 ± 0.030
TH0727/00	24	32 ± 1	0.967 ± 0.030
TH0728/00	24	30 ± 1	0.980 ± 0.030
TH0733/00	24	49 ± 1	1.015 ± 0.030
TH0735/00	24	44 ± 1	0.998 ± 0.030
TH0738/00	24	39 ± 1	1.000 ± 0.030
TH0744/00	24	49 ± 1	1.060 ± 0.030

**N.B.:** DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

**WARNING:** ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

COMPANY WITH  
MANAGEMENT SYSTEM  
- UNI EN ISO 9001 -  
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio  
Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18  
tel. +39 051 770 511 - fax +39 051 777 437  
www.sayerlack.com  
Cod. Fisc. e Reg. Impr. Bo 08866930152  
P. IVA: IT 00494251200 - R.E.A. n. 313180  
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

CODE	SHELF-LIFE (months)	SOLIDS CONTENT	SPECIFIC GRAVITY
TH0746/00	24	37 ± 1	1.020 ± 0.030
TH0748/00	24	28 ± 1	0.950 ± 0.030
TH0755/00	24	27 ± 1	0.970 ± 0.030
TH0756/00	6	75 ± 3	1.170 ± 0.030
TH0759/00	24	24 ± 1	0.930 ± 0.030
TH0760/00	24	42 ± 1	1.012 ± 0.030
TH0761/00	24	50 ± 1	1.070 ± 0.030
TH0620/00	24	26 ± 1	0,950 ± 0,030
TH0765/00	24	35 ± 1	0.982 ± 0.030
TH0767/00	24	23 ± 1	0.950 ± 0.030
TH0773/00	24	28 ± 1	0.940 ± 0.030
TH0775/00	24	28 ± 1	0.950 ± 0.030
TH0779/00	24	27 ± 1	0.970 ± 0.030
TH0780/00	24	28 ± 1	0.960 ± 0.030
TH0781/00	24	70 ± 2	1.150 ± 0.030
TH0784/00	24	29 ± 1	0.960 ± 0.010
TH0787/00	24	28 ± 1	0.950 ± 0.030
TH0788/00	24	34 ± 1	1.000 ± 0.030
TH0790/00	24	36 ± 1	0.950 ± 0.030
TH0793/00	24	25 ± 1	0.934 ± 0.030
TH0799/00	24	28 ± 1	0.948 ± 0.030
TH0801/00	24	24 ± 1	0.940 ± 0.030
TH0805/00	24	24 ± 1	0.940 ± 0.030
TH0808/00	24	23 ± 1	0.940 ± 0.030

**N.B.:** DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.  
**WARNING:** ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

COMPANY WITH  
MANAGEMENT SYSTEM  
- UNI EN ISO 9001 -  
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio  
Via del Fiffò, 12 - 40065 Pianoro (BO) - Italia - C.P. 18  
tel. +39 051 770 511 - fax +39 051 777 437  
www.sayerlack.com  
Cod. Fisc. e Reg. Impr. Bo 08866930152  
P. IVA: IT 00494251200 - R.E.A. n. 313180  
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

CODE	SHELF-LIFE (months)	SOLIDS CONTENT	SPECIFIC GRAVITY
TH0825/00	24	40 ± 1	0.980 ± 0.030
TH0925/00	24	26 ± 1	0.960 ± 0.030
TH1400/00	24	50 ± 1	1.059 ± 0.030
TH2513/00	24	31 ± 1	0.965 ± 0.030
TH2520/00	24	34 ± 1	0.940 ± 0.030
TH2526/00	24	27 ± 1	0.940 ± 0.030
TH2530/00	12	75 ± 1	1.070 ± 0.030
TH2533/00	24	27 ± 1	0.965 ± 0.030
TH2537/00	24	29 ± 1	1.020 ± 0.030
TH2569/00	24	18 ± 1	0.950 ± 0.030
TH2580/00	24	20 ± 1	1.001 ± 0.030
TH2587/00	24	20 ± 1	1.001 ± 0.030

**Shelf-life of isocyanate hardeners is two years as of the date of packaging.** If the product is properly stored and sealed in its original package, shelf-life can be extended for one year more, however a preliminary test is strongly recommended.

Isocyanate hardeners are affected by humidity, therefore packages shall be hermetically sealed and kept dry. Once the package has been opened, the product shall be used up within the same day.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.  
WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.