

DECORATIVE CANVAS

DESCRIPTION:

HV'Art Decorative Canvas is a waterborne Colour coat, designed for use over GSP or GSU, to produce a tight base for successful application of Artistic Finishes via a Glaze medium.

Application of Decorative Canvas allows the full benefits of Open-Time Glaze to be realised.

It produces a consistent sealed base without creating issues of adhesion or preventing proper drying of subsequent coats.

GLOSS LEVEL:

Decorative Canvas is manufactured as 50% sheen, producing a dense base for application of Glaze.

COLOURS:

Decorative Canvas is available in the full mixed colour spectrum, to assist with creating a background of whatever tone required.

AREA OF USE:

Wall surfaces, ceilings, any interior substrate previously primed with GSP or GSU, requiring the ideal surface for decorative Glaze.

METHOD OF APPLICATION:

Synthetic brush & fine haired rollers

MIXING PROCEEDURE:

Ready to use, can be thinned with drinking water up to 10% for increased flow if needed.

TECHNICAL CHARACTERISTICS:

Solid content (%) 34

Specific gravity (kg/l) 1.05

Viscosity (DIN4) 150seconds.

VOC Content: 37 g/ltr

SUBSTRATE:

Surfaces previously prepared with GSP / GSP+

RECOAT:

With HV'Art Open-Time Glaze,

DRYING:

Touch dry (room temperature): 2 hours

Sandable (room temperature): 4 hours

Drying times are indicative because they depend on temperature, humidity, & importantly air flow conditions.

Drying of waterborne products must take place at temperatures not below 15°C and at a relative humidity preferably not exceeding 85%. Out of these limits, there is a slowing down of the drying and/or formation of a less hard and resistant film. It is always advisable for drying to be forced, with air previously de-humidified and warm (20-30°C).