

Aquapeel

Product code A4605

Formerly known as Gramos Product Code 6121

Water based peelable coating



PRODUCT DESCRIPTION

AQUAPEEL is a white pigmented, water based peelable protective coating and is designed for application to paint spray booth walls, etc, so that overspray deposits can be removed quickly and easily.

FEATURES & BENEFITS

- * Dense white film
- * Easily peelable, good resistance to most paint overspray.
- * Thixotropic nature minimises 'running'
- * No flammability or toxicity problems.
- * Equipment cleaned with water - no use of thinners.
- * Economical.

DIRECTIONS FOR USE

Must be used as supplied and applied through normal pressure-fed spraying equipment, bearing in mind the following :

1. A 0.5" (13mm) internal bore fluid pipe should be utilised to permit fast throughput of the material.
2. The fluid tip on the spray gun should be at least 110 thou(2.8mm).
3. Use maximum fluid pressure available, normally around 40 psi (2.5 bar) with 60-80 psi (4-5 bar) air pressure.

Ensure that all equipment is washed out with water before use, and is free from thinners, etc, which will cause coagulation of the emulsion.

A double-pass application should give approximately 4 thou (0.1mm) dry film thickness and a coverage of about 5 square metres per litre.

Drying time:- Approximately 2-3 hours with good air circulation at normal room temperature (20 degrees C).

SPECIAL STORAGE

Protect from frost.

HEALTH AND SAFETY INFORMATION – SEE SEPARATE HEALTH AND SAFETY SHEET

GRAMOS APPLIED LTD

Spring Road, Smethwick, West Midlands. B66 1PT.

Tel: 0121 525 4000 / 0121 524 1000 Fax: 0121 525 4950 / 0121 525 4919

E-mail: info@gramos-applied.com website: www.gramos-applied.com

All recommendations made and information supplied are to assist customers, they do not infer any legal warranty or liability.
Printed in the UK. 11/2003 Issue No. 1 Page 1 of 1