Version number 5 Printing date 12.03.2020 Revision: 10.03.2020

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: AMOTHERM WOOD 450 SB A (1:1)
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category

PROC11 Non industrial spraying

PROC10 Roller application or brushing

PROC7 Industrial spraying

· Application of the substance / the mixture Antifire paint

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

J.F. AMONN srl div. Color

via cima i prà, 7

32014 Ponte nelle Alpi (BL)

ITALIA

Distributor:

J.F. Amonn s.r.l./GmbH

I-39100 Bolzano/Bozen

Via Altmann 12 Altmannstraße

Tel.: +39 0471 904-911 - Fax.: +39 0471 910-449

Informing department:

Product safety department.

tecnical department Color Division

phone: +39 0437 98411

email: laboratorio@amonncolor.com

· 1.4 Emergency telephone number:

National Poisons Information Service (NPIS)

In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

In N Ireland: Contact your local GP or pharmacist during normal hours; click here

(www.gpoutofhours.hscni.net/) for GP services Out-of-Hours.

In Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment. P241

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.03.2020 Version number 5 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
E	CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
Ε	CAS: 13674-84-5 EINECS: 237-158-7 Reg.nr.: 01-2119486772-26-0005	Tris (2-chlorometiletil)phosphate Acute Tox. 4, H302	3-7%
Ε	CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	1.5-3%
R	Reg.nr.: 01-2119976378-19-0000	Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids Skin Irrit. 2, H315; Skin Sens. 1, H317	0.5-1.5%

[•] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents

Water.

Water with a full water jet.

- 5.2 Special hazards arising from the substance or mixture
 - No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GB

Printing date 12.03.2020 Version number 5 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: No special measures required.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers:

Store in well closed containers in a cool, well ventilated area. Direct sunshine should be avoided.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters

on control paramotors				
· Components with limit values that require monitoring at the workplace:				
123-86-4 n-butyl acetate (10-25%)				
WEL Short-term value: 966 mg/m³, 200 ppm				
Long-term value: 724 mg/m³, 150 ppm				

108-65-6 2-methoxy-1-methylethyl acetate (0.5-1.5%)

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

· DNELs

123-86-4 n-butyl acetate

Orai	Long-term exposure, systemic effects	2 mg/kg bw/day (ver)
	Acute, systemic effects	2 mg/kg/day (Ver)
Dermal	Long-term exposure, systemic effects	11 mg/kg bw/day (Arb)
		6 mg/kg bw/day (Ver)
	Acute, local effects	11 mg/kg (Arb)
	Acute, systemic effects	6 mg/kg/day (Ver)
Inhalative	Long-term exposure, systemic effects	300 mg/m³ (Arb)
		35.7 mg/m³ (Ver)
	Long-term exposure, local effects	600 mg/m³ (Arb)
		35.7 mg/m³ (Ver)
	Acute, systemic effects	300 mg/m³ (Arb)
		300 mg/m³ (Ver)
	Acute, local effects	600 mg/m³ (Arb)

(Contd. on page 4)

Printing date 12.03.2020 Version number 5 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

		(Contd. of page 3)	
		300 mg/m³ (Ver)	
108-65-6	2-methoxy-1-methylethyl acetate		
Oral	Long-term exposure, systemic effects		
Dermal	Long-term exposure, systemic effects		
		320 mg/kg bw/day (Ver)	
Inhalative	Long-term exposure, systemic effects	• · · /	
		33 mg/m³ (Ver)	
	Long-term exposure, local effects	33 mg/m³ (Ver)	
	Acute, local effects	550 mg/m³ (Arb)	
PNECs			
123-86-4	n-butyl acetate		
PNEC 0.1	18 mg/l (freshwater)		
0.018 mg/l (Marine Water)			
35	35.6 mg/l (sewage traetmant plant microorganisms)		
0.3	36 mg/l (sporadic release)		
PNEC 0.0	0903 mg/kg (soil)		
0.9	981 mg/kg (sediment, freshwater)		
0.0	.0981 mg/kg (sediment, marine water)		
108-65-6	2-methoxy-1-methylethyl acetate		
PNEC 0.6	IEC 0.635 mg/l (freshwater)		
0.0	0635 mg/l (Marine Water)		
100 mg/l (sewage traetmant plant microorganisms)		ganisms)	
PNEC 0.2	29 mg/kg (soil)		
3.2	29 mg/kg (sediment, freshwater)		
0.3	329 mg/kg (sediment, marine water)		

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

· Breathing equipment:

- Face mask - term filter unit (EN 140):

Filter type A (gas and organic vapours - boiling point >65°C)

· Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

Rubber gloves

Chloroprene rubber, CR

PVC gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Gauze goggles

(Contd. on page 5)

Printing date 12.03.2020 Version number 5 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

· Body protection: Light weight protective clothing

(Contd. of page 4)

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Whitish
Odour: Solvent-like
Odour threshold: Not determined.

• pH-value: Not determined.

Change in condition

Melting point/freezing point: Not determined Initial boiling point and boiling range: 126 °C

· Flash point: 27 °C

· Inflammability (solid, gaseous) Not applicable.

· Ignition temperature: 415 °C

· **Decomposition temperature:** Not determined.

· Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Critical values for explosion:

Lower: 1.2 Vol % Upper: 7.5 Vol %

· Vapour pressure at 20 °C: 15 hPa

Density at 20 °C
 Relative density
 Vapour density
 Evaporation rate
 1.128 g/cm³
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

dynamic: Not determined. kinematic: Not determined.

· Solvent content:

 Organic solvents:
 27.6 %

 VOC (EU)
 302.5 g/l

 Solids content:
 72.4 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

__

Printing date 12.03.2020 Version number 5 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:			
123-86-4 i	123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (rat)	
Dermal	LD50	>14,000 mg/kg (rab)	
Inhalative	LC50/4 h	>23.4 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)	
13674-84-	13674-84-5 Tris (2-chlorometiletil)phosphate		
Oral	LD50	500 mg/kg (ATE)	
108-65-6 2	108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	37.5 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
123-86-4 n-butyl acetate		
LC50 96 h	18 mg/l (fish)	
LC50 21 d	43.5 mg/l (aquatic invertebrates)	
LOEC 21 d	47.6 mg/l (aquatic invertebrates)	
EC50 48 h	44 mg/l (aquatic invertebrates)	
EC50 72h	246 mg/l (Alga)	
EC50 96 h	18 mg/l (fish)	
EC50 21 d	34.2 mg/l (aquatic invertebrates)	
ErC50 48 h	392 mg/l (Alga)	
ErC50 24 h	335 mg/l (Alga)	
NOEC 21 d	23.2 mg/l (aquatic invertebrates)	
NOEC 48 h	196 mg/l (Alga)	
NOEC 24 h	196 mg/l (Alga)	
108-65-6 2-methoxy-1-methylethyl acetate		
LC50 96 h	180 mg/l (fish)	
LC50 14 d	63.5 mg/l (fish)	
LOEC 96 h	>1,000 mg/l (Alga)	
EC50 48 h	>500 mg/l (aquatic invertebrates)	
EC50 21 d	>100 mg/l (aquatic invertebrates)	
ErC50 96 h	>1,000 mg/l (Alga)	
Wachstum (EbCx) 10% 30 min	>1,000 mg/l (Microorganisms)	
NOEC 96 h	100 mg/l (fish)	
NOEC 14 d	47.5 mg/l (fish)	
12.2 Persistence and degradability No further relevant information available.		

(Contd. on page 7)

Printing date 12.03.2020 Version number 5 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

(Contd. of page 6)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must be specially treated under adherence to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1263

14.2 UN proper shipping name

· ADR 1263 PAINT
· IMDG, IATA PAINT

- · 14.3 Transport hazard class(es)
- · ADR



ClassLabel3 (F1) Flammable liquids.

· IMDG, IATA



ClassLabel3 Flammable liquids.3

· 14.4 Packing group

· ADR, IMDG, IĂTA | |||

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

Kemler Number: 30
EMS Number: F-E,S-D
Stowage Category A

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

(Contd. on page 8)

Version number 5 Revision: 10.03.2020 Printing date 12.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

· Transport/Additional information:	(Contd. of page 1
ADR	5 1
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000
	ml
Transport category	3
· Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
Excepted quantities (EQ)	· · · · · · · · · · · · · · · · ·
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008 GHS label elements
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations

The product is subject to classification in accordance with the prevailing version of the regulations on hazardous materials.

· Technical instructions (air):

Class	Share in %
NK	23.0

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

Version number 5 Printing date 12.03.2020 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

(Contd. of page 8)

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - oral – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Annex: Exposure scenario

- · Short title of the exposure scenario
- Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC11 Non industrial spraying

PROC10 Roller application or brushing

PROC7 Industrial spraying

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure

No special measures required.

Use only on hard ground.

Other operational conditions affecting worker exposure

Avoid contact with eyes.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Tightly sealed safety glasses.

- Face mask - term filter unit (EN 140):

Filter type A (gas and organic vapours - boiling point >65°C)

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Measures for consumer protection Ensure adequate labelling.
- · Environmental protection measures
- · Water

No special measures required.

Do not allow to reach sewage system.

· Soil Prevent contamination of soil.

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.03.2020 Version number 5 Revision: 10.03.2020

Trade name: AMOTHERM WOOD 450 SB - A (1:1)

(Contd. of page 9)

- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- Guidance for downstream users No further relevant information available.

GB